

PRODUCT DATA SHEET

Reviewed 01/02/2016



YOU CAN'T BUY A BETTER PAINT FOR LESS!™



Alkali Resistant Plaster Primer

SECTION A:	DESCRIPTION A solvent-base pigmented primer recommended for both interior and exterior plaster. With alkali-resistance for use on sound cement, concrete and brick substrates. Provides adhesion for subsequent top-coats and provides good opacity over most surfaces. Do not apply to damp surfaces (e.g. newly rendered plaster or cement). This product must be used in conjunction with either Excelsior Bonding Liquid or Excelsior Surfcon if the surface is very powdery or friable. Not suitable for Rhinolite or Gypsum plaster.
SECTION B:	COMPOSITION Modified Alkali resin in Hydrocarbon solvent.
SECTION C:	PHYSICAL PROPERTIES Colour: White Appearance: Dries to a matt finish Viscosity: 75 - 85 Ku @ 25°C. S.G.: 1.20 - 1.25 Mass Solids: 47 - 52% Volume Solids: 28 - 33% Shelf Life: 12 months Storage Conditions: Away from direct sunlight, heat and/or naked flame Pack Size: 1l, 5l, 20l, 200l Drying time: Touch-dry 4 hours, hard dry 18 hours @ 25°C. Recoating time: 18 Hours Spread Ratio: 4 - 8m ² /l
SECTION D:	APPLICATION PROPERTIES Product is supplied ready-for-use, but can be thinned with turpentine ± 10% for better penetration. Apply by a brush or roller also by spray.
SECTION E:	CLEANING Wash implements with turpentine while still wet.
SECTION F:	PRECAUTION Flash point: 43°C (contains flammable solvent) Toxicity: See M.S.D.S. (contains flammable solvent)
SECTION G:	NOTE No guarantees are implied by the recommendations contained herein; since the data sheet is issued for information only. Method of application, surface cleanliness, conditions of use etc. are beyond our control.