

PRODUCT DATA SHEET

Reviewed 01/02/2016



YOU CAN'T BUY A BETTER PAINT FOR LESS!™



Aqua-Repel

SECTION A:	DESCRIPTION A solvent-based, clear, transparent, silicone based water repellent for application to concrete, cement, brickwork or other porous substrates which dries to a matt clear finish. The product penetrates deep into the painted surface and provides an impenetrable barrier through which moisture cannot travel. NB!! This product CANNOT be overcoated as subsequent coats will not adhere. This product also offers stain resistance.
SECTION B:	COMPOSITION Modified silicone in solvent.
SECTION C:	PHYSICAL PROPERTIES Colour: Clear Appearance: Transparent matt varnish Viscosity: 20" FC4 @ 25°C S.G.: 1.03 - 1.08 Shelf Life: 12 Months Storage Conditions: Normal Pack Size: 1l, 5l, 20l
SECTION D:	APPLICATION PROPERTIES Method: Brush or spray (for spray thin with up to 20% turpentine). Roller not recommended as poor penetration occurs. Spreading Rate: 6 - 8m ² /l depending on substrate porosity Number of coats: Two (recommended) Drying Time @ 25°C: Touch dry 2/4 hours, hard dry 16 hours Overcoating Time @ 25°C: 4hrs Thinning: Turpentine where necessary Cleaning Solvent: Turpentine Recommended systems: As described above
SECTION E:	PRECAUTION Flash point: 35°C (refer to M.S.D.S.) Toxicity: See M.S.D.S.
SECTION F:	SURFACE PREPARATION New surfaces - make surfaces are free from moisture prior to painting.
SECTION G:	NOTE No guarantees are implied by the recommendations contained herein; since the data sheet is issued for information only.
Method	of application, surface cleanliness, conditions of use etc. are beyond our control.