

PRODUCT DATA SHEET

Reviewed 01/02/2016



YOU CAN'T BUY A BETTER PAINT FOR LESS!™



Face Brick Dressing

SECTION A:	DESCRIPTION An extremely durable weather resistant gloss varnish for use on interior and exterior brickwork and masonry work.
SECTION B:	COMPOSITION Oil based resin
SECTION C:	PHYSICAL PROPERTIES Colour: Clear Appearance: Transparent gloss varnish Viscosity: 60" FC4 @ 25°C S.G.: 0.89 - 0.94 Mass Solids: 41 - 46% Volume Solids: 32 - 37% Shelf Life: 12 Months Storage Conditions: Normal Pack Size: 1l, 5l
SECTION D:	APPLICATION PROPERTIES Method: Brush or spray (for spray thin with up to 20% turpentine). Or by roller application Spreading Rate: 8 - 10 m ² /l. Depending on porosity Number of coats: 2 Drying Time @ 25°C: Touch dry 2/4 hours, hard dry 16 hours Overcoating Time @ 25°C: 4hrs Thinning: Turpentine where necessary Cleaning Solvent: Turpentine Recommended systems: As described above Dry Film Thickness: 22 microns
SECTION E:	PRECAUTION Flash point: 23°C (refer to M.S.D.S.) Toxicity: See M.S.D.S.
SECTION F:	SURFACE PREPARATION - Apply to a surface that is free from dust, dirt or grease and without moisture. - Dilute first coat with 10% turpentine to allow better penetration. - NB!! This product requires annual maintenance of recoating to maintain its gloss and durability on exterior surfaces.
SECTION G:	NOTE No guarantees are implied by the recommendations contained herein; since the data sheet is issued for information only. Method of application, surface cleanliness, conditions of use etc. are beyond our control. Face Brick Dressing requires regular annual recoats to maintain the gloss appearance.