

PRODUCT DATA SHEET

Reviewed 01/02/2016



YOU CAN'T BUY A BETTER PAINT FOR LESS!™



Glaze Coat Clear

SECTION A:	DESCRIPTION	
	A transparent paint effect glaze.	
SECTION B:	COMPOSITION	
	Water-Based Emulsions and various additives.	
SECTION C:	PHYSICAL PROPERTIES	
	Colour:	Clear
	Appearance:	Milky liquid
	Gloss:	80% @ 60°
	Viscosity:	85 - 90 Ku @ 25°C
	S.G.:	1.00 - 1.05
	Mass Solids:	39 - 44%
	Volume Solids:	37 - 42%
	Shelf Life:	12 Months
	Storage Conditions:	Normal
	Pack Size:	1l
SECTION D:	APPLICATION PROPERTIES	
	Method:	Brush or spray (for spray thin with up to 20% water). Roller not recommended.
	Number of coats:	2 coats (recommended). Up to 4 coats
	Drying Time @ 25°C:	Touch dry 1 hour, hard dry 4 hours
	Overcoating Time @ 25°C:	4hrs
	Thinning:	Water where necessary
	Cleaning Solvent:	Water
	Recommended systems:	As described above
SECTION E:	PRECAUTION	
	Flash point:	Non flammable (refer to M.S.D.S.)
	Toxicity:	See M.S.D.S.
SECTION F:	SURFACE PREPARATION	
	Surfaces must be sound, clean dry (moisture content below 15%) before painting. One part of Acrylic paint: SUPA SATIN, SUPA MATT, PAVING ACRYLIC, SATIN ROOF or WEATHERFLEX. One part Glaze Coat Clear. One and a half parts water. This is only an approximate measure: By adding less of the Glaze the pigment concentration will be higher and the formulation will dry faster.	
	NEW WORK	
	- Apply acrylic base coat of selected colour and leave to cure.	
	- Use glaze mixture according to technique requirements	
	- Recoating: Treat as new work.	
	LIMITATIONS	
	- Cannot be used over enamel paint.	
	- Cannot be mixed with enamel paint.	
	- Can only be applied over properly prepared surfaces.	
	- The mixing ratio is dependant on the required technique used.	
SECTION G:	NOTE	
	No guarantees are implied by the recommendations contained herein; since the data sheet is issued for information only. Method of application, surface cleanliness, conditions of use etc. are beyond our control.	