

PRODUCT DATA SHEET

Reviewed 01/02/2016



YOU CAN'T BUY A BETTER PAINT FOR LESS!™



Pavecoat Acrylic Sealer

SECTION A:	DESCRIPTION A very hard, durable, adhesion promoted acrylic emulsion coating for cement and cement brick driveways. Recommended for porous paving bricks. (* Not suitable for smooth cement screeds or cement brick imprint paving).
SECTION B:	COMPOSITION Co-polymer emulsion based.
SECTION C:	PHYSICAL PROPERTIES Colour: As per colour card Appearance: Sheen Gloss: 10 - 20% @ 85° Viscosity: 85 - 90 Ku @ 25°C S.G.: 1.15 - 1.20 Mass Solids: 35 - 40% Volume Solids: 25 - 30% Shelf Life: 12 Months Storage Conditions: Normal Pack Size: 1l, 5l, 20l
SECTION D:	APPLICATION PROPERTIES Method: Brush or spray (for spray thin with up to 20% water). Spreading Rate: 6 - 8m/l, depending on surface texture Number of coats: 2 Drying Time @ 25°C: Minimum 48 hours before use - 1 week for hot car tyres Overcoating Time @ 25°C: 6hrs Thinning: Thin first coat with 10 - 20% water for better penetration. Cleaning Solvent: Water Recommended systems: As described above Dry Film Thickness: 100 microns (Min for 2 coats)
SECTION E:	PRECAUTION Flash point: Non flammable (refer to M.S.D.S.) Toxicity: See M.S.D.S.
SECTION F:	SURFACE PREPARATION Surfaces must be cleared of fungi and algae, sound, clean and dry (moisture content below 15%)

NEW SURFACES

- It is recommended that the first coat is diluted with 10 - 20% water to allow for better penetration into the substrate.
- Cement (Wood floated) Etch with 10 - 15% Pool acid (HCl) solution until free of efflorescence - rinse thoroughly.
- Cement Imprint Paving high pressure water jet cleaning. Allow to dry. Apply 1 coat Excelsior Surfcon.*
- Cement Pavers high pressure water jet cleaning. Allow to dry. Apply 1 coat Excelsior Surfcon.
- Friable cement Not recommended.
- Steel floated cement Not recommended.*
- Cement tiles Powdery and chalky surfaces: High pressure water jet cleaning required. Allow to dry. Apply 1 - 2 coat Excelsior SURFCON. Apply masking tape test before painting to ensure a sound surface.

RECOATING

- Driveways in good condition clean with Excelsior XL DEGREASER until dust and oil free and rinse thoroughly.
- Driveways in poor condition. Remove existing coating. If sound, treat as new Cement Imprint Paving or Cement Pavers.
- Cement paver in good condition. Clean with Excelsior XL DEGREASER until dust and oil free and rinse thoroughly.
- Cement paver in poor condition. Remove existing coating and treat as new cement paver. Apply masking take test before painting to ensure sound surface.

PRODUCT DATA SHEET

Reviewed 01/02/2016



YOU CAN'T BUY A BETTER PAINT FOR LESS!™

Pavecoat Acrylic Sealer.../continued

LIMITATIONS

- Can only be applied under recommended conditions.
- Adhesion to highly polished cement and gloss enamel floor paints is not good enough to ensure durability.
- Colour range limited to suitable colours for driveways, i.e. No bright colours.
- Could be slippery on steep inclines and when wet.
- Prone to marking with tyres.

SECTION G:

NOTE

No guarantees are implied by the recommendations contained herein; since the data sheet is issued for information only. Method of application, surface cleanliness, conditions of use etc. Are beyond our control.