

PRODUCT DATA SHEET

Reviewed 01/02/2016



YOU CAN'T BUY A BETTER PAINT FOR LESS!™



Premium Eggshell Enamel

SECTION A:	DESCRIPTION A premium quality eggshell enamel suitable for interior use as a protective or decorative coating. Leaves an attractive low-sheen washable finish that does not highlight imperfections on the surface. Ideal for bathrooms and kitchens, doors and door frames. Has excellent hiding power. Contains "STAIN SHIELD" additives to eliminate staining of the coating.
SECTION B:	COMPOSITION Alkyd Resin.
SECTION C:	PHYSICAL PROPERTIES Colour: White, Black, Tint Bases Appearance: Semi-gloss Gloss: 15 - 20% @ 60° Viscosity: 80 - 85 Ku @25°C S.G.: 1.37 - 1.42 Mass Solids: 68 - 73% Volume Solids: 48 - 53% Shelf Live: 12 Months Storage Conditions: Normal Pack Size: 1L, 5L
SECTION D:	APPLICATION PROPERTIES Method: Brush, Roller or Airless Spray Average Dft: 48 microns (Recommended) Spreading Rate: 8 - 10m ² /ℓ Wet Film Thickness: 45 - 50 microns Number of coats: 2 - 4 as required Drying Time: Surface 3 - 4hrs, hard 16hrs max Overcoating Time: Between 16 - 72hrs Cleaning Solvent: Excelsior Turps Recommended Systems: As a finishing and decorative coating on previously painted or new surface which have been well prepared or primed, for Interior use.
SECTION E:	PRECAUTION Flash point: Below 45°C Toxicity: Normal when used in well ventilated areas
SECTION F:	SURFACE PREPARATION NEW WOOD WORK Rub down with fine sandpaper, seal knots with knotting. Prime with Excelsior PINK WOOD PRIMER follow with one coat Excelsior UNIVERSAL UNDERCOAT. NEW IRON & STEEL Remove rust, oil & grease and then Prime with: - Excelsior AQUA METALPRIME water-based primer (New Formulation!). - Alkyd based Excelsior GP RED OXIDE PRIMER or Excelsior ZP PRIMER (with anti-corrosive zincphosphate pigments) followed with one coat Excelsior UNIVERSAL UNDERCOAT. NEW GALVANISED IRON Remove storage oil with GI CLEANER, apply one coat of Excelsior AQUA METALPRIME anti-corrosive primer, and follow with one coat Excelsior UNIVERSAL UNDERCOAT.



YOU CAN'T BUY A BETTER PAINT FOR LESS!™

Premium Eggshell Enamel.../continued

NEW PLASTER

Allow plaster to dry. Apply one coat either:

- Alkyd Excelsior PLASTER PRIMER (low alkalinity) recommended for interior plaster or,
- Excelsior PLIOLITE PLASTER PRIMER (Goodyear France technology) for maximum priming benefits (high alkalinity) recommended for exterior plaster.

PREVIOUSLY PAINTED EMULSION (PVA/ACRYLIC) SURFACES

- Loose material must be removed with sandpaper.
- Powdery surfaces must be sealed with Excelsior SURFCON (Surface Conditioner).
- Dirt or grime to be removed with sugar soap.

PREVIOUSLY PAINTED ENAMEL (HI-GLOSS OR EGGSHELL) SURFACES

- Sandpaper thoroughly
- Apply directly to a clean dirt and grease free surface.

IMPORTANT !!

PREMIUM EGGSHELL ENAMEL IS SUITABLE FOR INTERIOR USE ONLY.

SECTION F:

NOTE

Note for exterior use. touching up will lead to gloss variations. No guarantees are implied by the recommendations contained herein; since the data sheet is issued for information only. Method of application, surface cleanliness, conditions of use etc. are beyond our control.