

# PRODUCT DATA SHEET

Reviewed 01/02/2016



YOU CAN'T BUY A BETTER PAINT FOR LESS!™

## Premium Supa Matt Acrylic

SECTION A:	<b>DESCRIPTION</b> A premium quality matt acrylic paint for interior and exterior surfaces of the highest quality formulated to exceed the specification of S.A.B.S.1586 Grade 2, with excellent durability. Available in popular standard colours and in thousands of others. Imparts a washable matt finish. Contains SILICONE SHIELD™ which is a Silicone Resin additive for facades that need a long-lasting, multiple-protection barrier which lets water vapour escape to the outside of the building. The silicone resin emulsion paint protects walls while at the same time - lets them breathe. This eliminates the problem of rising damp
SECTION B:	<b>COMPOSITION</b> Pure acrylic emulsion paint.
SECTION C:	<b>PHYSICAL PROPERTIES</b> Colour: White, Colour Card, Tint Bases Appearance: Matt Gloss: < 10% @60° Viscosity: 90 - 105 Ku @ 25°C S.G.: 1.50 - 1.55% Mass Solids: 60 - 65% Volume Solids: 40 - 45% Shelf Life: 12 Months Storage Conditions: Normal Pack Size: 1l, 5l, 20l
SECTION D:	<b>APPLICATION PROPERTIES</b> Method: Brush, airless spray or roller Spreading Rate: 7 - 9m <sup>2</sup> /l Number of coats: 2 Drying Time @ 25°C: Hard 4hrs (depending on moisture and humidity). Allow 14 days to cure before washing. Overcoating Time @ 25°C: 4hrs Thinning: Not Applicable Cleaning Solvent: Water Recommended systems: As described above
SECTION E:	<b>PRECAUTION</b> Flash point: Water-based Toxicity: See M.S.D.S.
SECTION F	<b>SURFACE PREPARATION</b> - All surfaces to be thoroughly clean, dry and free from grease, dirt or flaking paint. - All loosely adhering material and powder such as distemper or lime must be removed, and a coat of Excelsior SURFCON (Surface Conditioner) applied and allowed to dry (± 18 hours). <b>GALVANISED IRON</b> - Remove storage oil with GI CLEANER and prime with one coat of Excelsior AQUA METALPRIME anti-corrosive primer. <b>MILD STEEL</b> - Prime with Excelsior H2O PRIMER RED OXIDE PRIMER etching water-based primer. (NEW FORMULATION!!) - Alkyd based Excelsior GP RED OXIDE PRIMER or Excelsior ZP PRIMER (with anti-corrosive zinc-phosphate pigments). <b>FRESH PLASTER</b> Once plaster is completely dry. Apply one coat of either: - Excelsior AQUA-PLASTER PRIMER (water-based).



YOU CAN'T BUY A BETTER PAINT FOR LESS!™

## Premium Supa Matt Acrylic.../continued

or Excelsior PLIOLITE PLASTER PRIMER (Goodyear France technology) (solvent-based).  
or Excelsior ALKALI RESISTANT PLASTER PRIMER (solvent-based).

### PREVIOUSLY PAINTED EMULSION (PVA/ACRYLIC) SURFACES

- Loose material must be removed with sandpaper.
- Powdery surfaces sealed with Excelsior SURFCON (surface conditioner).
- Dirt or grime to be removed with sugar soap.

### PREVIOUSLY PAINTED ENAMEL (Hi-gloss or Eggshell) SURFACES

- Sandpaper thoroughly
- Apply one coat of Excelsior UNIVERSAL UNDERCOAT and allow  $\pm 18$ hr to dry.

### IMPORTANT!

- Stir well before use.
- Allow 7 days for paint to cure fully before washing.

### SECTION F

### NOTE

No guarantees are implied by the recommendations contained herein; since the data sheet is issued for information only. Method of application, surface cleanliness, conditions of use etc. are beyond our control.