

PRODUCT DATA SHEET

Reviewed 01/02/2016



YOU CAN'T BUY A BETTER PAINT FOR LESS!™



Tennis Court Dressing

SECTION A:	DESCRIPTION A fast drying water-based coating specially formulated for marking asphalt tennis courts with a matt non-skid finish. The product has excellent water and alkali-resistance.
SECTION B:	COMPOSITION Acrylic co-polymer
SECTION C:	PHYSICAL PROPERTIES Colour: Red, Green Appearance: Matt finish Gloss: <15% @ 85° Viscosity: 75 - 95 Ku @ 25°C S.G.: 1.15 - 1.20 Mass Solids: 35 - 40% Volume Solids: 25 - 30% Shelf Life: 12 Months Storage Conditions: Normal Pack Size: 5ℓ, 20ℓ
SECTION D:	APPLICATION PROPERTIES Method: Brush or Roller (Recommended application by brush for maximum film build) Recommended Average Dft: 55 microns per coat Spreading Rate: 6 - 8m ² /ℓ Wet Film Thickness: 100 - 120 microns per coat Recommended No of coats: 1 - 2 as required Drying Time: Surface 30mins, hard 4hrs max Overcoating Time: 4 hours minimum Thinning: Not Recommended (water if necessary) Cleaning Solvent: Water
SECTION E:	SURFACE PREPARATION Clean the surface thoroughly removing all dust and dirt with sweeping and rinsing with clean water. Ensure surface is allowed to dry completely prior to painting. No priming is required. On new surfaces the product can be thinned by 10% with water to aid penetration into the surface. Apply an undiluted second coat. Apply the first coat (and subsequent coats) with a block brush to work in the paint properly into the surface ensuring a proper film thickness.
SECTION F:	PRECAUTION Not suitable for application to steel surfaces (unless properly primed) Flash point: N/A Toxicity: See M.S.D.S.
SECTION G:	NOTE No guarantees are implied by the recommendations contained herein ;since the data sheet is issued for information only. Method of application, surface cleanliness, conditions of use etc. are beyond our control.